	SAFETY DATA SHEET	Page : 1 / 16
		Revision nr : 1.0
	Rely T25 B-side Rely OEM B-side	Issue date : 26/01/2023
		Supersedes :

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Rely T25 B-side
Rely OEM B-side
UFI : U127-RSY7-N20V-2MQ6 (Rely OEM B-side)

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use, Industrial use
Use of the substance/mixture : Polymers for tyrefill applications

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Carpenter Belgium n.v.
Wijnendalestraat 171
8800 Roeselare - Belgium
T 051/23 02 11
Info.be@carpenter.com

1.4. Emergency telephone number

Emergency number : Chemtrec LCC: USA +1 800 424 9300 / INT +1 703 527 3887
This telephone number is available 24 hours per day, 7 days per week.

Carpenter Ltd, Glossop, UK - +44 (0)1457861141

Country	Official advisory body	Address	Emergency number


SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute Tox. 4 (Inhalation) H332
Carc. 1B H350
Repr. 2 H361d
STOT RE 2 H373
Aquatic Acute 1 H400
Aquatic Chronic 1 H410

Full text of H- and EUH-statements: see section 16

	SAFETY DATA SHEET	Page : 2 / 16
		Revision nr : 1.0
	Rely T25 B-side Rely OEM B-side	Issue date : 26/01/2023
		Supersedes :

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word :

Danger

Contains :

Residues (petroleum), catalytic reformer fractionator

Hazard statements (CLP) :

H332 - Harmful if inhaled.
 H350 - May cause cancer.
 H361d - Suspected of damaging the unborn child.
 H373 - May cause damage to organs through prolonged or repeated exposure.
 H410 - Very toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) :

P201 - Obtain special instructions before use.
 P260 - Do not breathe vapours.
 P273 - Avoid release to the environment.
 P280 - Wear protective gloves, protective clothing, eye protection, face protection.
 P308+P313 - IF exposed or concerned: Get medical advice, medical attention.
 P391 - Collect spillage.
 P501 - Dispose of contents and container to an approved waste disposal plant.

Extra phrases : EUH208 - Contains m-phenylenediamine, dibutyltin dilaurate. May produce an allergic reaction.
 Restricted to professional users.

2.3. Other hazards

Other hazards :

Results of PBT and vPvB assessment : Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Substance name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Residues (petroleum), catalytic reformer fractionator	(CAS-No.) 64741-67-9 (EC-No.) 265-069-3 (EC Index) 649-048-00-X (REACH-no) 01-2119488737-18-xxxx	60 – 65	Acute Tox. 4 (Inhalation), H332 Carc. 1B, H350 Repr. 2, H361d STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410



SAFETY DATA SHEET

Page : 3 / 16

Revision nr : 1.0

Issue date : 26/01/2023

Rely T25 B-side Rely OEM B-side

Supersedes :

m-phenylenediamine	(CAS-No.) 108-45-2 (EC-No.) 203-584-7 (EC Index) 612-147-00-3 (REACH-no) 01-2119491149-30-xxxx	< 1	Muta. 2, H341 Acute Tox. 3 (Inhalation), H331 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Oral), H301 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
dibutyltin dilaurate	(CAS-No.) 77-58-7 (EC-No.) 201-039-8 (EC Index) 050-030-00-3 (REACH-no) 01-2119496068-27-xxxx	< 0,3	Eye Irrit. 2, H319 Skin Sens. 1, H317 Muta. 2, H341 Repr. 1B, H360FD STOT SE 1, H370 STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- Additional advice : First aider: Pay attention to self-protection!. Concerning personal protective equipment to use, see section 8. Never give anything by mouth to an unconscious person. In case of doubt or persistent symptoms, consult always a physician. Show this safety data sheet to the doctor in attendance.
- Inhalation : Remove casualty to fresh air and keep warm and at rest. In case of doubt or persistent symptoms, consult always a physician.
- Skin contact : Remove contaminated clothing and shoes. Gently wash with plenty of soap and water. In case of doubt or persistent symptoms, consult always a physician.
- Eyes contact : Rinse immediately carefully and thoroughly with eye-bath or water. Remove contact lenses, if present and easy to do. Continue rinsing. In case of doubt or persistent symptoms, consult always a physician.
- Ingestion : Rinse mouth thoroughly with water. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

- Inhalation : Harmful if inhaled. Inhalation of vapours may cause respiratory irritation.
- Skin contact : Exposure may produce an allergic reaction. May cause skin irritation. The following symptoms may occur: Redness, pain.
- Eyes contact : May cause eye irritation. The following symptoms may occur: Redness, pain.
- Ingestion : May cause gastrointestinal irritation, nausea, vomiting and diarrhoea.
- Chronic symptoms : May cause cancer. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.


SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : carbon dioxide (CO₂), powder, alcohol-resistant foam, water spray.
- Unsuitable extinguishing media : Strong water jet.

5.2. Special hazards arising from the substance or mixture

- Specific hazards : Not flammable. Heating will cause a rise in pressure with a risk of bursting.
- Hazardous decomposition products in case of fire : Carbon oxides (CO, CO₂).

	SAFETY DATA SHEET	Page : 4 / 16
		Revision nr : 1.0
		Issue date : 26/01/2023
	Rely T25 B-side Rely OEM B-side	Supersedes :

5.3. Advice for firefighters

- Firefighting instructions : Evacuate area. Use water spray or fog for cooling exposed containers. Contain the extinguishing fluids by bunding. Prevent fire fighting water from entering the environment.
- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus.
- Other information : Do not allow run-off from fire-fighting to enter drains or water courses. Dispose of waste in accordance with environmental legislation.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- For non-emergency personnel : Evacuate unnecessary personnel. Keep upwind. Provide adequate ventilation. Do not breathe vapours. Avoid contact with skin, eyes and clothing. Wear recommended personal protective equipment. Concerning personal protective equipment to use, see section 8. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

6.1.2. For emergency responders

- For emergency responders : Ensure procedures and training for emergency decontamination and disposal are in place. Concerning personal protective equipment to use, see section 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Stop leak if safe to do so. Dam up the liquid spill. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Recover large spills by pumping (use an explosion proof or hand pump). Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

Concerning personal protective equipment to use, see section 8. Concerning disposal elimination after cleaning, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Provide adequate ventilation. Do not breathe vapours. Avoid contact with skin, eyes and clothing. Use personal protective equipment as required. Concerning personal protective equipment to use, see section 8. Take any precaution to avoid mixing with Incompatible materials, Refer to Section 10 on Incompatible Materials. Ensure proper process control to avoid excess waste discharge (temperature, concentration, pH, time). Avoid release to the environment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Hygiene measures : Keep good industrial hygiene. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product. Keep away from food, drink and animal feedingstuffs. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in a dry, cool and well-ventilated place. Do not store near or with any of the incompatible materials listed in section 10. Bund storage facilities to prevent soil and water pollution in the event of spillage.



SAFETY DATA SHEET

Page : 5 / 16

Revision nr : 1.0

Issue date : 26/01/2023

Rely T25 B-side Rely OEM B-side

Supersedes :

- Heat and ignition sources : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Special rules on packaging : After use replace the closing cap immediately. Keep container tight closed. Containers which are opened should be properly resealed and kept upright to prevent leakage.
- Packaging materials : Keep only in the original container.

7.3. Specific end use(s)

Reference to other sections : 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

m-phenylenediamine (108-45-2)		
Belgium	OEL TWA	0,1 mg/m ³
Denmark	OEL TWA [1]	0,1 mg/m ³
Greece	OEL TWA	0,1 mg/m ³
Ireland	OEL TWA [1]	0,1 mg/m ³
Ireland	OEL STEL	0,3 mg/m ³ (calculated)
Latvia	OEL TWA	0,1 mg/m ³
Lithuania	IPRV (OEL TWA)	0,1 mg/m ³
Portugal	OEL TWA	0,1 mg/m ³
Spain	VLA-ED (OEL TWA) [1]	0,1 mg/m ³
Norway	Grenseverdi (OEL TWA) [1]	0,1 mg/m ³
Norway	Korttidsverdi (OEL STEL)	0,3 mg/m ³ (value calculated)
Switzerland	MAK (OEL TWA) [1]	0,1 mg/m ³ (aerosol, inhalable dust, vapour)
Australia	OES TWA [1]	0,1 mg/m ³
Canada (Quebec)	VEMP (OEL TWA)	0,1 mg/m ³
USA - ACGIH	ACGIH OEL TWA	0,1 mg/m ³

- Additional information : Recommended monitoring procedures :. Personal air monitoring. Room air monitoring

8.2. Exposure controls

- Engineering measure(s) : Organisational measures to prevent/limit releases, dispersion and exposure. See Section 7 for information on safe handling. Emergency safety showers should be available in the immediate vicinity of any potential exposure.
- Personal protective equipment : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.



SAFETY DATA SHEET

Page : 6 / 16

Revision nr : 1.0

Issue date : 26/01/2023

Rely T25 B-side
Rely OEM B-side

Supersedes :

Hand protection	: Wear chemically resistant gloves (tested to EN374) . Suitable material: Not determined. Thickness : Not determined. Breakthrough time : Not determined. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.
Eye protection	: Use suitable eye protection (EN166): Safety glasses
Body protection	: Wear suitable protective clothing. Overalls, apron and boots recommended. Wear long sleeves
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment. Half-face mask (DIN EN 140). full face mask (DIN EN 136). Filter type: ABEK (EN 14387). The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used. (EN 137)
Thermal hazard protection	: Not required for normal conditions of use. Use dedicated equipment.
Environmental exposure controls	: Avoid release to the environment. Comply with applicable Community environmental protection legislation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: dark brown.
Odour	: Petroleum.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting / freezing point	: < -10 °C (1013 hPa)
Freezing point	: No data available
Initial boiling point and boiling range	: 150 – 450 °C (1013 hPa)
Flash point	: > 200 °C
Auto-ignition temperature	: 220 – 250 °C
Decomposition temperature	: No data available
Flammability	: Not applicable,liquid
Vapour pressure	: 0,02 – 0,791 kPa
Vapour density	: No data available
Relative density	: 1,01 – 1,06 (25 °C)
Solubility	: Insoluble in water. miscible with most organic solvents.
Partition coefficient n-octanol/water	: 3,43 (22 °C)
Kinematic viscosity	: 200 – 500 cPs
Dynamic viscosity	: No data available
Explosive properties	: Not applicable. The study does not need to be conducted because there are no chemical groups associated with explosive properties present in the molecule.
Oxidising properties	: Not applicable. The classification procedure needs not to be applied because there are no chemical groups present in the molecule which are associated with oxidising properties.
Explosive limits	: No data available
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable



SAFETY DATA SHEET

Page : 7 / 16

Revision nr : 1.0

Issue date : 26/01/2023

**Rely T25 B-side
Rely OEM B-side**

Supersedes :

Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

Other properties : acid number : 11,80 - 12, 80 mg KOH/g (Rely T25 B-side) / 12,83 - 14,83 mg KOH/g (Rely OEM B side)

SECTION 10: Stability and reactivity

10.1. Reactivity

None under normal conditions. Reference to other sections: 10.4 & 10.5.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. See Section 7 for information on safe handling.

10.5. Incompatible materials

Strong oxidizing agents. See Section 7 for information on safe handling.

10.6. Hazardous decomposition products

Reference to other sections 5.2.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity : Harmful if inhaled.

ATE CLP (gases)	4500 ppmv/4h
ATE CLP (vapours)	11 mg/l/4h
ATE CLP (dust,mist)	1,5 mg/l/4h

Residues (petroleum), catalytic reformer fractionator (64741-67-9)

LD50/oral/rat	4320 mg/kg (OECD 401)
LD50/dermal/rabbit	2000 (OECD 434)
LC50/inhalation/4h/rat	4100 mg/l (EPA OTS 798.1150)

m-phenylenediamine (108-45-2)

LD50/oral/rat	204 mg/kg
LD50/dermal/rat	1100 mg/kg
LC50/inhalation/4h/rat	3,2 mg/l/4h



SAFETY DATA SHEET

Page : 8 / 16

Revision nr : 1.0

Issue date : 26/01/2023

Rely T25 B-side Rely OEM B-side

Supersedes :

dibutyltin dilaurate (77-58-7)

LD50/oral/rat 45 mg/kg

LD50/dermal/rat > 2000 mg/kg

LD50/dermal/rabbit 630 mg/kg

Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met) pH: No data available
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met) pH: No data available
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: May cause cancer.
Reproductive toxicity	: Suspected of damaging the unborn child.
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)

Rely T25 B-side Rely OEM B-side

Kinematic viscosity 200 – 500 mm²/s

Other adverse effects	: May cause damage to organs through prolonged or repeated exposure. Suspected of damaging the unborn child. May cause cancer.
Other information	: Symptoms related to the physical, chemical and toxicological characteristics. For further information see section 4.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties	: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %
--	--

11.2.2 Other information

Other adverse effects	: May cause damage to organs through prolonged or repeated exposure, Suspected of damaging the unborn child, May cause cancer
Other information	: Symptoms related to the physical, chemical and toxicological characteristics, For further information see section 4

SECTION 12: Ecological information

12.1. Toxicity

Environmental properties : Very toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term (acute) : Very toxic to aquatic life.

Hazardous to the aquatic environment, long-term (chronic) : Very toxic to aquatic life with long lasting effects.

Residues (petroleum), catalytic reformer fractionator (64741-67-9)

LC50 - Fish [1] 79 mg/l (Oncorhynchus mykiss)



SAFETY DATA SHEET

Page : 9 / 16

Revision nr : 1.0

Issue date : 26/01/2023

Rely T25 B-side
Rely OEM B-side

Supersedes :

EC50 - Crustacea [1]	0,22 mg/l (Daphnia Magna)
EC50 72h - Algae [1]	> 1000 mg/l (Tetrahymena pyriformis)

m-phenylenediamine (108-45-2)

LC50 - Fish [1]	1600 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
EC50 - Crustacea [1]	5,9 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 96h - Algae [1]	2,4 mg/l (Species: Pseudokirchneriella subcapitata)

dibutyltin dilaurate (77-58-7)

LC50 - Fish [1]	3,1 mg/l (Zebra Fish)
EC50 - Crustacea [1]	463 µg/l (Daphnia magna)
EC50 72h - Algae [1]	> 1 mg/l (Desmodesmus subspicatus)

12.2. Persistence and degradability

Rely T25 B-side Rely OEM B-side	
Persistence and degradability	No additional information available.

12.3. Bioaccumulative potential

Rely T25 B-side Rely OEM B-side	
Partition coefficient n-octanol/water	3,43 (22 °C)
Bioaccumulative potential	No additional information available.

m-phenylenediamine (108-45-2)

Partition coefficient n-octanol/water	-0,3
---------------------------------------	------

dibutyltin dilaurate (77-58-7)


Partition coefficient n-octanol/water	4,44 (at 20.8 °C (at pH 6.1-6.3))
---------------------------------------	-----------------------------------

12.4. Mobility in soil

Rely T25 B-side Rely OEM B-side	
Mobility in soil	No data available

12.5. Results of PBT and vPvB assessment

Rely T25 B-side Rely OEM B-side	
Results of PBT assessment	Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

	SAFETY DATA SHEET	Page : 10 / 16
		Revision nr : 1.0
	Rely T25 B-side Rely OEM B-side	Issue date : 26/01/2023
		Supersedes :

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

12.7. Other adverse effects

Other adverse effects : No data available

SECTION 13: Disposal considerations






13.1. Waste treatment methods

Product/Packaging disposal recommendations : Avoid release to the environment. Dispose of empty containers and wastes safely. See Section 7 for information on safe handling. Refer to manufacturer/supplier for information on recovery/recycling. Recycling is preferred to disposal or incineration. If recycling is not possible, eliminate in accordance with local valid waste disposal regulations. Handle contaminated packages in the same way as the substance itself. Dispose of contaminated materials in accordance with current regulations. Beware of residues or vapours which remain in the drums.

European waste catalogue (2001/573/EC, 75/442/EEC, 91/689/EEC) : This material and its container must be disposed of as hazardous waste. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
3082	3082	3082	3082	3082
14.2. UN proper shipping name				
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Residues (petroleum), catalytic reformer fractionator)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Residues (petroleum), catalytic reformer fractionator)	Environmentally hazardous substance, liquid, n.o.s. (Residues (petroleum), catalytic reformer fractionator)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Residues (petroleum), catalytic reformer fractionator)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Residues (petroleum), catalytic reformer fractionator)
Transport document description				
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Residues (petroleum), catalytic reformer fractionator), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Residues (petroleum), catalytic reformer fractionator), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (Residues (petroleum), catalytic reformer fractionator), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Residues (petroleum), catalytic reformer fractionator), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Residues (petroleum), catalytic reformer fractionator), 9, III
14.3. Transport hazard class(es)				
9	9	9	9	9
				



SAFETY DATA SHEET

Page : 11 / 16

Revision nr : 1.0

Issue date : 26/01/2023

**Rely T25 B-side
Rely OEM B-side**

Supersedes :


ADR	IMDG	IATA	ADN	RID
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes
No supplementary information available				

14.6. Special precautions for user

Special precautions for user : No data available

- Overland transport

Classification code (ADR) : M6
Special provisions : 274, 335, 375, 601
Limited quantities (ADR) : 5I
Excepted quantities (ADR) : E1
Packing instructions (ADR) : P001, IBC03, LP01, R001
Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T4
Portable tank and bulk container special provisions (ADR) : TP1, TP29
Tank code (ADR) : LGBV
Vehicle for tank carriage : AT
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Special provisions for carriage - Loading, unloading and handling (ADR) : CV13
Hazard identification number (Kemler No.) : 90
Orange plates :



Tunnel restriction code : -
EAC code : •3Z

- Transport by sea

Special provisions (IMDG) : 274, 335, 969
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : LP01, P001
Special packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1, TP29
EmS-No. (Fire) : F-A



SAFETY DATA SHEET

Page : 12 / 16

Revision nr : 1.0

Issue date : 26/01/2023

Rely T25 B-side Rely OEM B-side

Supersedes :

EmS-No. (Spillage) : S-F

Stowage category (IMDG) : A

- Air transport

PCA Excepted quantities (IATA) : E1

PCA Limited quantities (IATA) : Y964

PCA limited quantity max net quantity (IATA) : 30kgG

PCA packing instructions (IATA) : 964

PCA max net quantity (IATA) : 450L

CAO packing instructions (IATA) : 964

CAO max net quantity (IATA) : 450L

Special provisions (IATA) : A97, A158, A197, A215

ERG code (IATA) : 9L

- Inland waterway transport

Classification code (ADN) : M6

Special provisions (ADN) : 274, 335, 375, 601

Limited quantities (ADN) : 5 L

Excepted quantities (ADN) : E1

Carriage permitted (ADN) : T

Equipment required (ADN) : PP

Number of blue cones/lights (ADN) : 0

- Rail transport

Classification code (RID) : M6

Special provisions (RID) : 274, 335, 375, 601

Limited quantities (RID) : 5L

Excepted quantities (RID) : E1

Packing instructions (RID) : P001, IBC03, LP01, R001

Special packing provisions (RID) : PP1

Mixed packing provisions (RID) : MP19

Portable tank and bulk container instructions (RID) : T4

Portable tank and bulk container special provisions (RID) : TP1, TP29

Tank codes for RID tanks (RID) : LGBV

Transport category (RID) : 3

Special provisions for carriage – Packages (RID) : W12


Special provisions for carriage - Loading, unloading and handling (RID) : CW13, CW31

Colis express (express parcels) (RID) : CE8

Hazard identification number (RID) : 90

14.7. Maritime transport in bulk according to IMO instruments

Code: IBC : No data available.

	SAFETY DATA SHEET	Page : 13 / 16
		Revision nr : 1.0
		Issue date : 26/01/2023
	Rely T25 B-side Rely OEM B-side	Supersedes :

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Listed on REACH Annex XVII (Restriction Conditions). The following restrictions are applicable:

28. Substances which are classified as carcinogen category 1A or 1B in Part 3 of Annex VI to Regulation (EC) No 1272/2008 and are listed in Appendix 1 or Appendix 2, respectively.	Residues (petroleum), catalytic reformer fractionator
3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	Rely T25 B-side Rely OEM B-side ; Residues (petroleum), catalytic reformer fractionator ; dibutyltin dilaurate
3(c) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	Rely T25 B-side Rely OEM B-side ; Residues (petroleum), catalytic reformer fractionator ; dibutyltin dilaurate
30. Substances which are classified as reproductive toxicant category 1A or 1B in Part 3 of Annex VI to Regulation (EC) No 1272/2008 and are listed in Appendix 5 or Appendix 6, respectively.	dibutyltin dilaurate

Contains no substance(s) listed on the REACH Candidate List

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

15.1.2. National regulations

France

No ICPE	Installations classées Désignation de la rubrique	Code Régime	Rayon
4510.text	Dangereux pour l'environnement aquatique de catégorie aiguë 1 ou chronique 1.		
4510.1	La quantité totale susceptible d'être présente dans l'installation étant : 1. Supérieure ou égale à 100 t Quantité seuil bas au sens de l'article R. 511-10 : 100 t. Quantité seuil haut au sens de l'article R. 511-10 : 200 t.	A	1
4510.2	La quantité totale susceptible d'être présente dans l'installation étant : 2. Supérieure ou égale à 20 t mais inférieure à 100 t Quantité seuil bas au sens de l'article R. 511-10 : 100 t. Quantité seuil haut au sens de l'article R. 511-10 : 200 t.	DC	

Germany

Regulatory reference	: WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1)
German storage class (LGK)	: LGK 12 - Non-combustible liquids
Hazardous Incident Ordinance (12. BImSchV)	: Listed in the 12. BImSchV (Annex I) under: 1.3.1 Quantity threshold for operational area under § 1 para. 1 - Sentence 1: 100000 kg - Sentence 2: 200000 kg

Netherlands

Waterbezwaarlijkheid	: categorie Z(1) - niet-afbreekbare stoffen met gevaarlijke eigenschappen voor mens en milieu (carcinogeniteit/ mutageniteit/ reprotoxiciteit/ bioaccumulerend vermogen/ toxiciteit of persistentie)
SZW-lijst van kankerverwekkende stoffen	: Residues (petroleum), catalytic reformer fractionator is listed
SZW-lijst van mutagene stoffen	: None of the components are listed



SAFETY DATA SHEET

Page : 14 / 16

Revision nr : 1.0

Issue date : 26/01/2023

Rely T25 B-side
Rely OEM B-side

Supersedes :

SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed

SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : dibutyltin dilaurate is listed

SZW-lijst van reprotoxische stoffen – Ontwikkeling : dibutyltin dilaurate is listed

Denmark

Recommendations Danish Regulation : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

Not applicable

SECTION 16: Other information

Abbreviations and acronyms:

	ABM = Algemene beoordelingsmethodiek
	ADN = Accord Européen relatif au Transport International des Marchandises Dangereuses par voie de Navigation du Rhin
	ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
	CLP = Classification, Labelling and Packaging Regulation according to 1272/2008/EC
	IATA = International Air Transport Association
	IMDG = International Maritime Dangerous Goods Code
	LEL = Lower Explosive Limit/Lower Explosion Limit
	UEL = Upper Explosion Limit/Upper Explosive Limit
	REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
	BTT = Breakthrough time (maximum wearing time)
	DMEL = Derived Minimal Effect level
	DNEL = Derived No Effect Level
	EC50 = Median Effective Concentration
	EL50 = Median effective level
	ErC50 = EC50 in terms of reduction of growth rate
	ErL50 = EL50 in terms of reduction of growth rate
	EWC = European waste catalogue
	LC50 = Median lethal concentration
	LD50 = Median lethal dose
	LL50 = Median lethal level
	NA = Not applicable
	NOEC = No observed effect concentration
	NOEL: no-observed-effect level
	NOELR = No observed effect loading rate
	NOAEC = No observed adverse effect concentration
	NOAEL = No observed adverse effect level
	N.O.S. = Not Otherwise Specified
	OEL = Occupational Exposure Limits - Short Term Exposure Limits (STELs)
	PNEC = Predicted No Effect Concentration
	Quantitative structure-activity relationship (QSAR)
	STOT = Specific Target Organ Toxicity
	TWA = time weighted average
	VOC = Volatile organic compounds
	WGK = Wassergefährdungsklasse (Water Hazard Class under German Federal Water Management Act)



SAFETY DATA SHEET

Page : 15 / 16

Revision nr : 1.0

Issue date : 26/01/2023

Rely T25 B-side Rely OEM B-side

Supersedes :


Sources of key data used to compile the datasheet : Supplier information. ECHA (European Chemicals Agency). LOLI.

Training advice : Training staff on good practice. Manipulations are to be done only by qualified and authorised persons.

Other information : Classification - Assessment method: CLP Calculation method (Article 9).
Physicochemical hazard assessment: Information given is based on tests on the mixture itself.

Full text of H- and EUH-statements:

	Restricted to professional users
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1B	Carcinogenicity, Category 1B
EUH208	Contains m-phenylenediamine, dibutyltin dilaurate. May produce an allergic reaction.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H360FD	May damage fertility. May damage the unborn child.
H361d	Suspected of damaging the unborn child.
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
Muta. 2	Germ cell mutagenicity, Category 2
Repr. 1B	Reproductive toxicity, Category 1B
Repr. 2	Reproductive toxicity, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 1	Specific target organ toxicity – single exposure, Category 1

	SAFETY DATA SHEET	Page : 16 / 16
		Revision nr : 1.0
		Issue date : 26/01/2023
	Rely T25 B-side Rely OEM B-side	Supersedes :

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878
Classification according to Regulation (EC) No. 1272/2008 [CLP]
Labelling according to Regulation (EC) No. 1272/2008 [CLP]

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.